YPS Generators



GENERATING SET MODEL (YP15) Output Ratings Prime Standby 230-400V, 3ph, 50Hz, 1500 rpm 15 KVA 17 KVA 12 KW 13.6 KW 480V, 3phm 60Hz, 1800 rpm 18 KVA 20 KVA 14.4 KW 16 KW

Applicable Voltages: 220/127 V at 60 Hz only (Consult your dealer for more details)

Ratings at 0.8 Power Factor

ENGINE / TECHNICAL DATA		
Engine Make	Perkins	
Engine Model	403A-15G2	
Governing Class	ISO 8528/1	
Number of Cylinders	3	
Cylinder Arrangement	Vertical in line	
Bore and Stroke mm	84 x 90	
Displacement / Cubic Capacity liters	1.496	
Induction System	Naturally Aspirated	
Cycle	4 stroke	
Combustion System	Indirect Injection	
Compression Ratio	22.5:1	
Rotation	Anti-clockwise (viewed from flywheel)	
Cooling System	Water - cooled	
Frequency and Engine Speed	50Hz & 1500rpm	60Hz &1800rpm
	Prime Standby	Prime Standby
Gross Engine Power kW (hp)	14 (18) 15 (20)	16(22) 18 (24)

Fuel Consumption I/hr(US gal/hr)

FUEL SYSTEM

	Engine Speed	1500 rpm
on	Standby	4.1 L
	Prime Power	3.7
	75% of Prime Power	2.8
	50% of Prime Power	2.0
Fuel Tank C)pen /Close	97 L / 114 L

DIMENSIONS AND WEIGHT

Generator Type	Length mm	Width mm	Height mm	Weight kg
Open Type	1500	610	1000	485
Close Type	1900	900	1450	835

15 KVA



GEN-SET CANOPY SPECIFICATIONS (OPTIONAL)		
Canopy Type	Acoustic / Weatherproof	
Anticorrosive Protection	Heat treated Galvanized Metal sheets	
Access Doors	4	
Drainage	Fuel & Water drainage	
Noise Level	66 dbA @ 7 meter	
Cable Access	Cable Inlet and Outlet	
Emergency Stop	External Emergency Puch Button	
ALTERNATOR DATA		
Make	Leroy Somer - TAL	
Model	LSA-TAL040D	
No. of Bearings	1	
Insulation Class	Н	
Total Harmonic Content	at no load<3% - on load <2%	
Wires	12	

Ingress Protection

Excitation System

Voltage Regulation (steady)

Winding Pitch

AVR Model

Overspeed



AREP & PMG Excitation System Available as Optional.

IP23

Shunt

2/3 (wdg M)

R220

2250 mn-1

± 2%

Make	Deep Sea
Model	DSE6110

Disclaimer: Younus Power Services have made efforts to ensure that the information in this data sheet is accurate but reserve the right to amend specifications and information without notice and without obligation or liability.