



GENERATING SET MODEL (YP400)

Output Ratings	Prime	Standby
380-415V, 3ph, 50Hz, 1500 rpm	400 KVA	450 KVA
	320 KW	360 KW
480V, 3phm 60Hz, 1800 rpm	400 KVA	438 KVA
	320 KW	350.4 KW

Applicable Voltages: 220/127 V at 60 Hz only (Consult your dealer for more details) Ratings at 0.8 Power Factor

ENGINE / TECHNICAL DATA

Engine Make	Perkins		
Engine Model	2206A-E13TAG3		
Governing Class	Electronic		
Number of Cylinders	6		
Cylinder Arrangement	Vertical line		
Bore and Stroke mm	130 x 157		
Displacement / Cubic Capacity liters	12.5		
Induction System	Turbocharged and air to air charge cooled		
Cycle	4 stroke		
Combustion System	Direct Injection		
Compression Ratio	16.3:1		
Rotation	Anti-clockwise (viewed on flywheel)		
Cooling System	Water – cooled		
Frequency and Engine Speed	50Hz & 1500rpm	60Hz & 1800rpm	
	Prime Standby	Prime	Standby
Gross Engine Power kW (hp)	368 (493)	413 (554)	373 (500) 407 (546)

FUEL SYSTEM

Fuel Consumption l/hr(US gal/hr)	Engine Speed	1500 rpm	1800 rpm
	Standby	90 (23.8)	87 (23.0)
	Prime Power	81 (21.4)	81 (21.4)
	75% of Prime Power	62 (16.1)	62 (16.4)
	50% of Prime Power	42 (11.1)	43 (11.4)
Fuel Tank Open /Close		950 L / 950 L	

DIMENSIONS AND WEIGHT

Generator Type	Length mm	Width mm	Height mm	Weight kg
Open Type	3400	1120	1940	3080
Close Type	4740	1600	2370	4530

GEN-SET CANOPY SPECIFICATIONS (OPTIONAL)

Canopy Type	Acoustic / Weatherproof
Anticorrosive Protection	Heat treated Galvanized Metal sheets
Access Doors	4
Drainage	Fuel & Water drainage
Noise Level	66 dbA @ 7 meter
Cable Access	Cable Inlet and Outlet
Emergency Stop	External Emergency Puch Button

ALTERNATOR DATA

Make	Leroy Somer - TAL
Model	LSA-TAL046I
No. of Bearings	1
Insulation Class	H
Total Harmonic Content	On load <2%
Wires	12
Ingress Protection	IP23
Excitation System	Shunt
Winding Pitch	2/3 (n° 6)
AVR Model	R250
Overspeed	2250 mn-1
Voltage Regulation (steady)	± 0.5%

AREP & PMG Excitation System Available as Optional.

CONTROL PANEL



Make	Deep Sea
Model	DSE6110

Disclaimer : Younus Power Services have made efforts to ensure that the information in this data sheet is accurate but reserve the right to amend specifications and information without notice and without obligation or liability.