

600 KVA





GENERATING SET MODEL (YP600)				
Output Ratings	Prime	Standby		
230-400V, 3ph, 50Hz, 1500 rpm	600 KVA	660 KVA		
	480 KW	528 KW		
480V, 3phm 60Hz, 1800 rpm	625 KVA	660 KVA		
	500 KW 528 KW			
Applicable Voltages: 220/127 V at 60 Hz only (Consult your dealer for more details)	Ratings at 0.8 Power Factor			
ENGINE / TECHNICAL DATA				
Engine Make	Perkins			
Engine Model	2806A-E18TAG1A			
Governing Class	ISO 8528-5 G3			
Number of Cylinders	6			
Cylinder Arrangement	Vertical line			
Bore and Stroke mm	145 x 183			
Displacement / Cubic Capacity liters	18.1			
Induction System	Turbocharged and air to air charge cooled			
Cycle	4 stroke			
Combustion System	Direct Injection			
Compression Ratio	14.5:1			
Rotation	Anti-clockwise (viewed on flywheel)			
Cooling System	Water – cooled			
Frequency and Engine Speed	50Hz & 1500rpm 60Hz &1800rpm			
	Prime Standby	Prime Standby		
Gross Engine Power kW (hp)	540 (724) 593 (795) 568(762) 623(835)			

GEN-SET CANOPY SPECIFICATIONS (OPTIONAL)			
Canopy Type	Acoustic / Weatherproof		
Anticorrosive Protection	Heat treated Galvanized Metal sheets		
Access Doors	4		
Drainage	Fuel & Water drainage		
Noise Level	66 dbA @ 7 meter		
Cable Access	Cable Inlet and Outlet		
Emergency Stop	External Emergency Puch Button		

ALTERNATOR DATA		
Make	Leroy Somer - TAL	
Model	LSA-TAL047E	
No. of Bearings	1	
Insulation Class	Н	
Total Harmonic Content	On load <2%	
Wires	12	
Ingress Protection	IP23	
Excitation System	Shunt	
Winding Pitch	2/3 (n° 6)	
AVR Model	R250	
Overspeed	2250 mn-1	
Voltage Regulation (steady)	± 0.5%	
AREP & PMG Excitation System Available as Optional.		

Fuel Consumption Standby

	Engine Speed	1500 rpm	1800 rpm
	Standby	134 (35.4)	141 (37.2)
	Prime Power	123 (32.5)	127 (33.5)
	75% of Prime Power	90 (23.8)	95 (25.1)
	50% of Prime Power	61 (16.1)	66 (17.4)

Fuel Tank Open /Close 950 L / 950 L

CONTROL PANEL



Make	Deep Sea
Model	DSE6110

Disclaimer: Younus Power Services have made efforts to ensure that the information in this data sheet is accurate but reserve the right to amend specifications and information without notice and without obligation or liability.

DIMENSIONS AND WEIGHT

FUEL SYSTEM

I/hr(US gal/hr)

Generator Type	Length mm	Width mm	Height mm	Weight kg
Open Type	3940	1550	2200	4760
Close Type	5530	1980	2460	6420